

Wall Mount Bracket



- Aluminum alloy construction
- Designed for reliability and aesthetics

Overview

It is ideal for mounting cameras and works in temperatures ranging from $-40\text{ }^{\circ}\text{C}$ to $+60\text{ }^{\circ}\text{C}$ ($-40\text{ }^{\circ}\text{F}$ to $+140\text{ }^{\circ}\text{F}$) and in environments with relative humidity of less than 90%.

Technical Specification

Structure

Material	Aluminum Alloy
Dimensions (L x W x H)	222.0 mm x 160.7 mm x 144.4 mm (8.66 in. x 6.33 in. x 5.68 in.)
Color	White
Net Weight	1.1 kg (2.42 lb)
Gross Weight	1.5 kg (3.31 lb)
Load Bearing	3.0 kg (6.61 lb)
Installation	Wall Mount
Screw Thread Type	G 3/4
Packaging Dimensions (L x W x H)	675.0 mm x 456.0 mm x 575.0 mm (26.57 in. x 17.95 in. x 22.64 in.)
Packaging Method	12 Pieces per Master Carton

Environment

Operating Temperature	$-40\text{ }^{\circ}\text{C}$ to $60\text{ }^{\circ}\text{C}$ ($-40\text{ }^{\circ}\text{F}$ to $140\text{ }^{\circ}\text{F}$)
Operating Humidity	< 90% (RH)
Storage Temperature	$-40\text{ }^{\circ}\text{C}$ to $60\text{ }^{\circ}\text{C}$ ($-40\text{ }^{\circ}\text{F}$ to $140\text{ }^{\circ}\text{F}$)
Storage Humidity	10% to 90% (RH)

Ordering Information

Type	Model	Description
Camera Mount	DH-PFB206W	Wall Mount Bracket
Package Contents	<ul style="list-style-type: none"> • Three (3) M4 x 10 Screws • Four (4) ST4 x 25 Screws • Four (4) Plastic Expansion Bolt • One (1) 3.0 Hex Wrench • One (1) Water Joint • One (1) Mounting Sticker 	

Dimensions

mm [in.]

